

DATASHEET

NI 9239

4 AI, ± 10 V, 24 Bit, 50 kS/s/ch Simultaneous



- BNC or screw-terminal connectivity
- Anti-alias filters
- 250 Vrms, CAT II, channel-to-channel isolation (screw terminal); 60 VDC, CAT I, channel-to-channel isolation (BNC)

The NI 9239 is an analog input module for use in NI CompactDAQ or CompactRIO systems. Each channel provides a ± 10 V measurement range at a 24-bit resolution. The NI 9239 outputs 50 kS/s of data at the maximum sampling rate. Designed for both speed and accuracy, the NI 9239 is an effective general-purpose analog module because of its resolution, sample rate, and input range.

| | |
|--|---|
|  | <p>Kit Contents</p> <ul style="list-style-type: none">• NI 9239• NI 9239 Getting Started Guide |
|  | <p>Accessories</p> <ul style="list-style-type: none">• NI 9971 Backshell Connector Kit (Screw Terminal)• EMI Suppression Ferrite (BNC) |

| C SERIES DIFFERENTIAL INPUT MODULE COMPARISON | | | | | | |
|---|---------------|----------|-------------|--------------|------------|--------------------------------------|
| Product Name | Signal Levels | Channels | Sample Rate | Simultaneous | Resolution | Connectivity |
| NI 9215 | ±10 V | 4 | 100 kS/s/ch | Yes | 16-Bit | Screw-Terminal, Spring-Terminal, BNC |
| NI 9220 | ±10 V | 16 | 100 kS/s/ch | Yes | 16-Bit | Spring-Terminal, DSUB |
| NI 9222 | ±10 V | 4 | 500 kS/s/ch | Yes | 16-Bit | Screw-Terminal, BNC |
| NI 9223 | ±10 V | 4 | 1 MS/s/ch | Yes | 16-Bit | Screw-Terminal, BNC |
| NI 9229 | ±60 V | 4 | 50 kS/s/ch | Yes | 24-Bit | Screw-Terminal, BNC |
| NI 9239 | ±10 V | 4 | 50 kS/s/ch | Yes | 24-Bit | Screw-Terminal, BNC |

NI C Series Overview



NI provides more than 100 C Series modules for measurement, control, and communication applications. C Series modules can connect to any sensor or bus and allow for high-accuracy measurements that meet the demands of advanced data acquisition and control applications.

- Measurement-specific signal conditioning that connects to an array of sensors and signals
- Isolation options such as bank-to-bank, channel-to-channel, and channel-to-earth ground
- -40 °C to 70 °C temperature range to meet a variety of application and environmental needs
- Hot-swappable

The majority of C Series modules are supported in both CompactRIO and CompactDAQ platforms and you can move modules from one platform to the other with no modification.

CompactRIO



CompactRIO combines an open-embedded architecture with small size, extreme ruggedness, and C Series modules in a platform powered by the NI LabVIEW reconfigurable I/O (RIO) architecture. Each system contains an FPGA for custom timing, triggering, and processing with a wide array of available modular I/O to meet any embedded application requirement.

CompactDAQ

CompactDAQ is a portable, rugged data acquisition platform that integrates connectivity, data acquisition, and signal conditioning into modular I/O for directly interfacing to any sensor or signal. Using CompactDAQ with LabVIEW, you can easily customize how you acquire, analyze, visualize, and manage your measurement data.



Software

LabVIEW Professional Development System for Windows




- Use advanced software tools for large project development
- Generate code automatically using DAQ Assistant and Instrument I/O Assistant
- Use advanced measurement analysis and digital signal processing
- Take advantage of open connectivity with DLLs, ActiveX, and .NET objects
- Build DLLs, executables, and MSI installers

NI LabVIEW FPGA Module




- Design FPGA applications for NI RIO hardware
- Program with the same graphical environment used for desktop and real-time applications
- Execute control algorithms with loop rates up to 300 MHz
- Implement custom timing and triggering logic, digital protocols, and DSP algorithms
- Incorporate existing HDL code and third-party IP including Xilinx IP generator functions
- Purchase as part of the LabVIEW Embedded Control and Monitoring Suite

NI LabVIEW Real-Time Module



- Design deterministic real-time applications with LabVIEW graphical programming
- Download to dedicated NI or third-party hardware for reliable execution and a wide selection of I/O
- Take advantage of built-in PID control, signal processing, and analysis functions
- Automatically take advantage of multicore CPUs or set processor affinity manually
- Take advantage of real-time OS, development and debugging support, and board support
- Purchase individually or as part of a LabVIEW suite

NI 9239 Input Circuitry



- Input signals on each channel are conditioned, buffered, and then sampled by an ADC.
- Each AI channel provides an independent signal path and ADC, enabling you to sample all channels simultaneously.

Filtering


The NI 9239 uses a combination of analog and digital filtering to provide an accurate representation of in-band signals and reject out-of-band signals. The filters discriminate between signals based on the frequency range, or bandwidth, of the signal. The three important bandwidths to consider are the passband, the stopband, and the anti-imaging bandwidth.

The NI 9239 represents signals within the passband, as quantified primarily by passband ripple and phase nonlinearity. All signals that appear in the alias-free bandwidth are either unaliased signals or signals that have been filtered by at least the amount of the stopband rejection.

Passband

The signals within the passband have frequency-dependent gain or attenuation. The small amount of variation in gain with respect to frequency is called the passband flatness. The digital filters of the NI 9239 adjust the frequency range of the passband to match the data rate. Therefore, the amount of gain or attenuation at a given frequency depends on the data rate.

Figure 1. Typical Passband Response for the NI 9239



Stopband

The filter significantly attenuates all signals above the stopband frequency. The primary goal of the filter is to prevent aliasing. Therefore, the stopband frequency scales precisely with the data rate. The stopband rejection is the minimum amount of attenuation applied by the filter to all signals with frequencies within the stopband.

Alias-Free Bandwidth

Any signals that appear in the alias-free bandwidth are not aliased artifacts of signals at a higher frequency. The alias-free bandwidth is defined by the ability of the filter to reject frequencies above the stopband frequency. The alias-free bandwidth is equal to the data rate minus the stopband frequency.

Data Rates

The frequency of a master timebase (f_M) controls the data rate (f_s) of the NI 9239. The NI 9239 includes an internal master timebase with a frequency of 12.8 MHz, but the module also can accept an external master timebase or export its own master timebase. To synchronize the data rate of an NI 9239 with other modules that use master timebases to control sampling, all of the modules must share a single master timebase source.

The following equation provides the available data rates of the NI 9239:

$$f_s = \frac{f_M \div 256}{n}$$

where n is any integer from 1 to 31.

However, the data rate must remain within the appropriate data rate range. When using the internal master timebase of 12.8 MHz, the result is data rates of 50 kS/s, 25 kS/s, 16.667 kS/s,

and so on down to 1.613 kS/s, depending on the value of n . When using an external timebase with a frequency other than 12.8 MHz, the NI 9239 has a different set of data rates.



Note The NI 9151 R Series Expansion chassis does not support sharing timebases between modules.

NI 9239 Specifications

The following specifications are typical for the range -40 °C to 70 °C unless otherwise noted. All voltages are relative to the AI- signal on each channel unless otherwise noted.



Caution Do not operate the NI 9239 in a manner not specified in this document. Product misuse can result in a hazard. You can compromise the safety protection built into the product if the product is damaged in any way. If the product is damaged, return it to NI for repair.

Input Characteristics

| | |
|--|--|
| Number of channels | 4 analog input channels |
| ADC resolution | 24 bits |
| Type of ADC | Delta-Sigma (with analog prefiltering) |
| Sampling mode | Simultaneous |
| Internal master timebase (f_M) | |
| Frequency | 12.8 MHz |
| Accuracy | ±100 ppm maximum |
| Data rate range (f_s) using internal master timebase | |
| Minimum | 1.613 kS/s |
| Maximum | 50 kS/s |
| Data rate range (f_s) using external master timebase | |
| Minimum | 390.625 S/s |
| Maximum | 51.2 kS/s |

Figure 2. Data Rates¹ (f_s)

$$\frac{f_M \div 256}{n}, n = 1, 2, \dots, 31$$

Input voltage ranges (AI+ to AI-)

| | |
|------------------------------|----------|
| Nominal | ±10 V |
| Typical | ±10.52 V |
| Minimum | ±10.3 V |
| Overvoltage protection | ±100 V |
| Input coupling | DC |
| Input impedance (AI+ to AI-) | 1 MΩ |

Table 1. NI 9239 Accuracy

| Measurement Conditions | | Percent of Reading (Gain Error) | Percent of Range ² (Offset Error) |
|---------------------------|---------------------------|------------------------------------|---|
| Calibrated | Typical (25 °C, ±5 °C) | ±0.03% | ±0.008% |
| | Maximum (-40 °C to 70 °C) | ±0.13% | ±0.06% |
| Uncalibrated ³ | Typical (25 °C, ±5 °C) | ±0.3% | ±0.11% |
| | Maximum (-40 °C to 70 °C) | ±1.4% | ±0.70% |

| | |
|---|--|
| Input noise | 70 μVrms |
| Stability | |
| Gain drift | ±5 ppm/°C |
| Offset drift | ±26 μV/°C |
| Post-calibration gain match (channel-to-channel, 20 kHz) | 0.22 dB maximum |
| Phase mismatch | |
| Channel-to-channel | 0.075°/kHz maximum |
| Module-to-module | $(0.075^\circ/\text{kHz} \cdot f_{in}) + (360^\circ \cdot f_{in}/f_M)$ |
| Phase nonlinearity ($f_s = 50$ kS/s) | 0.11° maximum |

¹ The data rate must remain within the appropriate data rate range.

² Range equals 10.52 V

³ Uncalibrated accuracy refers to the accuracy achieved when acquiring in raw or unscaled modes where the calibration constants stored in the module are not applied to the data.

Figure 3. Input delay

$$40 \frac{5}{512} / f_s + 3.3 \mu\text{s}$$

Passband

| | |
|-----------------------------|----------------------|
| Frequency | $0.453 \cdot f_s$ |
| Flatness ($f_s = 50$ kS/s) | ± 100 dB maximum |

Stopband

| | |
|--|-------------------|
| Frequency | $0.547 \cdot f_s$ |
| Rejection | 100 dB |
| Alias-free bandwidth | $0.453 \cdot f_s$ |
| -3 dB prefilter bandwidth ($f_s = 50$ kS/s) | 24.56 kHz |
| Crosstalk (1 kHz) | -130 dB |
| CMRR ($f_{in} = 60$ Hz) | 126 dB |
| SFDR (1 kHz, -60 dBFS) | 128 dBFS |
| Total Harmonic Distortion (THD) | |
| 1 kHz, -1 dBFS | -99 dB |
| 1 kHz, -20 dBFS | -105 dB |

MTBF

| | |
|-----------------------------|--|
| NI 9239 with screw terminal | 662,484 hours at 25 °C; Bellcore Issue 6, Method 1, Case 3, Limited Part Stress Method |
| NI 9239 with BNC | 864,132 hours at 25 °C; Bellcore Issue 6, Method 1, Case 3, Limited Part Stress Method |

Power Requirements**Power consumption from chassis**

| | |
|-----------------------------|--------------------|
| Active mode | |
| NI 9239 with screw terminal | 740 mW maximum |
| NI 9239 with BNC | 800 mW maximum |
| Sleep mode | 25 μ W maximum |

Thermal dissipation

| | |
|-----------------------------|----------------|
| Active mode | |
| NI 9239 with screw terminal | 760 mW maximum |
| NI 9239 with BNC | 820 mW maximum |
| Sleep mode | 16 mW maximum |

Physical Characteristics

If you need to clean the module, wipe it with a dry towel.



Tip For two-dimensional drawings and three-dimensional models of the C Series module and connectors, visit ni.com/dimensions and search by module number.

Screw-terminal wiring

| | |
|----------------------------|--|
| Gauge | 0.05 mm ² to 1.5 mm ² (30 AWG to 14 AWG) copper conductor wire |
| Wire strip length | 6 mm (0.24 in.) of insulation stripped from the end |
| Temperature rating | 90 °C minimum |
| Torque for screw terminals | 0.22 N · m to 0.25 N · m (1.95 lb · in. to 2.21 lb · in.) |
| Wires per screw terminal | One wire per screw terminal; two wires per screw terminal using a 2-wire ferrule |
| Ferrules | 0.25 mm ² to 1.5 mm ² |

Connector securement

| | |
|-----------------------------|---------------------------|
| Securement type | Screw flanges provided |
| Torque for screw flanges | 0.2 N · m (1.80 lb · in.) |
| Weight | |
| NI 9239 with screw terminal | 147 g (5.2 oz.) |
| NI 9239 with BNC | 169 g (6.0 oz.) |

NI 9239 with Screw Terminal Safety Voltages

Connect only voltages that are within the following limits:

Isolation

| | |
|-------------------------|--|
| Channel-to-channel | |
| Continuous | 250 Vrms, Measurement Category II |
| Withstand | 1,390 V, verified by a 5 s dielectric withstand test |
| Channel-to-earth ground | |
| Continuous | 250 Vrms, Measurement Category II |
| Withstand | 2,300 V, verified by a 5 s dielectric withstand test |

Measurement Category I is for measurements performed on circuits not directly connected to the electrical distribution system referred to as *MAINS* voltage. *MAINS* is a hazardous live electrical supply system that powers equipment. This category is for measurements of voltages from specially protected secondary circuits. Such voltage measurements include signal levels, special equipment, limited-energy parts of equipment, circuits powered by regulated low-voltage sources, and electronics.



Note Measurement Categories CAT I and CAT O are equivalent. These test and measurement circuits are not intended for direct connection to the *MAINS* building installations of Measurement Categories CAT II, CAT III, or CAT IV.



Caution If using in Division 2 or Zone 2 hazardous locations applications, do not connect the NI 9239 with screw terminal to signals or use for measurements within Measurement Categories II, III, or IV.

Measurement Category II is for measurements performed on circuits directly connected to the electrical distribution system. This category refers to local-level electrical distribution, such as that provided by a standard wall outlet, for example, 115 V for U.S. or 230 V for Europe.



Caution Do not connect the NI 9239 with screw terminal to signals or use for measurements within Measurement Categories III or IV.

NI 9239 with BNC Safety Voltages

Connect only voltages that are within the following limits:

Isolation

| Channel-to-channel | |
|-------------------------|--|
| Continuous | 60 VDC, Measurement Category I |
| Withstand | 1,000 V, verified by a 5 s dielectric withstand test |
| Channel-to-earth ground | |
| Continuous | 60 VDC, Measurement Category I |
| Withstand | 1,000 V, verified by a 5 s dielectric withstand test |

Measurement Category I is for measurements performed on circuits not directly connected to the electrical distribution system referred to as *MAINS* voltage. *MAINS* is a hazardous live electrical supply system that powers equipment. This category is for measurements of voltages from specially protected secondary circuits. Such voltage measurements include signal levels,

⁴ Channel-to-channel and channel-to-earth ground

special equipment, limited-energy parts of equipment, circuits powered by regulated low-voltage sources, and electronics.



Note Measurement Categories CAT I and CAT O are equivalent. These test and measurement circuits are not intended for direct connection to the MAINS building installations of Measurement Categories CAT II, CAT III, or CAT IV.



Caution Do not connect the NI 9239 with BNC to signals or use for measurements within Measurement Categories II, III, or IV.

Hazardous Locations

| | |
|---|---|
| U.S. (UL) | Class I, Division 2, Groups A, B, C, D, T4; Class I, Zone 2, AEx nA IIC T4 |
| Canada (C-UL) | Class I, Division 2, Groups A, B, C, D, T4; Class I, Zone 2, Ex nA IIC T4 |
| Europe (ATEX) and International (IECEx) | Ex nA IIC T4 Gc |

Safety and Hazardous Locations Standards

This product is designed to meet the requirements of the following electrical equipment safety standards for measurement, control, and laboratory use:

- IEC 61010-1, EN 61010-1
- UL 61010-1, CSA 61010-1
- EN 60079-0:2012, EN 60079-15:2010
- IEC 60079-0: Ed 6, IEC 60079-15; Ed 4
- UL 60079-0; Ed 5, UL 60079-15; Ed 3
- CSA 60079-0:2011, CSA 60079-15:2012



Note For UL and other safety certifications, refer to the product label or the [Online Product Certification](#) section.

Electromagnetic Compatibility

This product meets the requirements of the following EMC standards for electrical equipment for measurement, control, and laboratory use:

- EN 61326-1 (IEC 61326-1): Class A emissions; Industrial immunity
- EN 55011 (CISPR 11): Group 1, Class A emissions
- AS/NZS CISPR 11: Group 1, Class A emissions
- FCC 47 CFR Part 15B: Class A emissions
- ICES-001: Class A emissions



Note In the United States (per FCC 47 CFR), Class A equipment is intended for use in commercial, light-industrial, and heavy-industrial locations. In Europe,

Canada, Australia and New Zealand (per CISPR 11) Class A equipment is intended for use only in heavy-industrial locations.



Note Group 1 equipment (per CISPR 11) is any industrial, scientific, or medical equipment that does not intentionally generate radio frequency energy for the treatment of material or inspection/analysis purposes.



Note For EMC declarations and certifications, and additional information, refer to the [Online Product Certification](#) section.

CE Compliance

This product meets the essential requirements of applicable European Directives, as follows:

- 2014/35/EU; Low-Voltage Directive (safety)
- 2014/30/EU; Electromagnetic Compatibility Directive (EMC)
- 94/9/EC; Potentially Explosive Atmospheres (ATEX)

Online Product Certification

Refer to the product Declaration of Conformity (DoC) for additional regulatory compliance information. To obtain product certifications and the DoC for this product, visit ni.com/certification, search by model number or product line, and click the appropriate link in the Certification column.

Shock and Vibration

To meet these specifications, you must panel mount the system.

Operating vibration

| | |
|----------------------------------|---|
| Random (IEC 60068-2-64) | 5 g _{rms} , 10 Hz to 500 Hz |
| Sinusoidal (IEC 60068-2-6) | 5 g, 10 Hz to 500 Hz |
| Operating shock (IEC 60068-2-27) | 30 g, 11 ms half sine; 50 g, 3 ms half sine; 18 shocks at 6 orientations |

Environmental

Refer to the manual for the chassis you are using for more information about meeting these specifications.

| | |
|---|---------------------------------|
| Operating temperature (IEC 60068-2-1, IEC 60068-2-2) | -40 °C to 70 °C |
| Storage temperature (IEC 60068-2-1, IEC 60068-2-2) | -40 °C to 85 °C |
| Ingress protection | IP40 |
| Operating humidity (IEC 60068-2-78) | 10% RH to 90% RH, noncondensing |

| | |
|-----------------------------------|--------------------------------|
| Storage humidity (IEC 60068-2-78) | 5% RH to 95% RH, noncondensing |
| Pollution Degree | 2 |
| Maximum altitude | 2,000 m |

Indoor use only.

Environmental Management

NI is committed to designing and manufacturing products in an environmentally responsible manner. NI recognizes that eliminating certain hazardous substances from our products is beneficial to the environment and to NI customers.

For additional environmental information, refer to the *Minimize Our Environmental Impact* web page at ni.com/environment. This page contains the environmental regulations and directives with which NI complies, as well as other environmental information not included in this document.

Waste Electrical and Electronic Equipment (WEEE)



EU Customers At the end of the product life cycle, all NI products must be disposed of according to local laws and regulations. For more information about how to recycle NI products in your region, visit ni.com/environment/weee.

电子信息产品污染控制管理办法（中国 RoHS）



中国客户 National Instruments 符合中国电子信息产品中限制使用某些有害物质指令 (RoHS)。关于 National Instruments 中国 RoHS 合规性信息，请登录 ni.com/environment/rohs_china。(For information about China RoHS compliance, go to ni.com/environment/rohs_china.)

Calibration

You can obtain the calibration certificate and information about calibration services for the NI 9239 at ni.com/calibration.

| | |
|----------------------|--------|
| Calibration interval | 1 year |
|----------------------|--------|

Refer to the *NI Trademarks and Logo Guidelines* at ni.com/trademarks for information on NI trademarks. Other product and company names mentioned herein are trademarks or trade names of their respective companies. For patents covering NI products/technology, refer to the appropriate location: **Help»Patents** in your software, the `patents.txt` file on your media, or the *National Instruments Patent Notice* at ni.com/patents. You can find information about end-user license agreements (EULAs) and third-party legal notices in the readme file for your NI product. Refer to the *Export Compliance Information* at ni.com/legal/export-compliance for the NI global trade compliance policy and how to obtain relevant HTS codes, ECCNs, and other import/export data. NI MAKES NO EXPRESS OR IMPLIED WARRANTIES AS TO THE ACCURACY OF THE INFORMATION CONTAINED HEREIN AND SHALL NOT BE LIABLE FOR ANY ERRORS. U.S. Government Customers: The data contained in this manual was developed at private expense and is subject to the applicable limited rights and restricted data rights as set forth in FAR 52.227-14, DFAR 252.227-7014, and DFAR 252.227-7015.

© 2016 National Instruments. All rights reserved.

375939B-02 Apr16